VARIABLE MULCHER





TACKLES THE TOUGHEST OF MULCHING JOBS

Whether you are tackling overgrown ditches, low level vegetation or whole tree removal, the Auger Torque Variable Mulcher attachments offer the ideal solution with perfect results.

Suitable for Excavators and Skidsteer Loaders, the Variable Mulcher provides a working width up to 1.5m, and has the unique feature of being able to change the whole tooth drum instead of individual teeth, saving a LOT of time in the process.

Hinged Door
- Easy access to tooth drum
- Help to contain mulching debris

Highly Engineered Gears and Bearings
- Large bearings for smooth running
- Concealed to prevent dust and dirt ingress



2 models available
- VM1000 offers a 1m width
- VM1500 offers a 1.5m width

Heavy Duty Construction
- Solid steel structure to tackle the most rigorous mulching tasks
- Low profile design for good visibility

Interchangeable Tooth Drum
- Swap the whole drum for out for different combinations
- Individual teeth can be replace if required
- A variety of teeth options available for different tasks

www.augertorque.com

CALL 01451 861652 | EMAIL sales@augertorque.com | OR CONTACT YOUR NEAREST DEALER

VARIABLE MULCHER

Features

- Replaceable toothed cutting drum
- Working width options of 1m and 1.5m
- Heavy duty steel construction
- Hinged door for easy drum access
- High quality motor and hoses
- Easy access maintenance panels

Applications

- Ground clearance
- Woodland pathway creation and maintenance
- Clear and maintain vegetation
- Tree and Hedge trimming
- Mulch trees and hedges down to ground level
- Fire break creation

Specifications

VM1000

Standard Gear Motor
Oil Pressure Range: 160 - 180 BAR (2320.6 - 2610.7 psi)
Optimum Oil Pressure: 180 BAR (2610.7 psi)
Oil Flow Range: 60 - 70 LPM (15.85 - 18.49 gpm)
Optimum Oil Flow: 70 LPM (18.49 gpm)

SUITABLE FOR EXCAVATORS
5T (11023 lbs) to 10T (22046 lbs)

SKIDSTEER COMPATIBLE
Suitable for machines that can obtain
the above pressures and flow rates

CUTTING
Drum Speed: up to 2400rpm (parent machine dependant)
Cutting drum width: 1000mm (40 in)
Processes trees up to 120 mm (5 in) diameter

DIMENSIONS
529mm x 1229mm x 794mm (h x w x d)
20.82in x 48.38in x 31.26in (h x w x d)

WEIGHT
400 kg (882 lbs)

VM1500

Standard Piston Motor
Oil Pressure Range: 220- 240 BAR (3190.8 - 3480-9 psi)
Optimum Oil Pressure: 240 BAR (3480.9 psi)
Oil Flow Range: 85 - 95 LPM (22.4 - 25.0 gpm)
Optimum Oil Flow: 95 LPM (25.0 gpm)

SUITABLE FOR EXCAVATORS
10T (22046 lbs) to 15T (33069 lbs)

SKIDSTEER COMPATIBLE
Suitable for machines that can obtain
the above pressures and flow rates

CUTTING
Drum Speed: up to 2400rpm (parent machine dependant)
Cutting drum width: 1500mm (60 in)
Processes trees up to 250 mm (10 in) diameter

DIMENSIONS
953mm x 1820mm x 994mm (h x w x d)
37.52in x 71.65in x 39.13in (h x w x d)

WEIGHT
800 kg (1763.7 lbs)







DEALER STAMP



Part of the Auger Torque landscaping range
STUMP PLANERS | LOG SPLITTERS | MULCHERS | HEDGE TRIMMERS | SWEEPER BROOMS